



PE-AX 5058 - 6405058

Product Description

Product suitable for: Extrusion, cast film and blow film

Recommended dosage : 0.25 - 3.0%

Carrier resin: LDPE

Concentrate of: Process aid

Typical Product Characteristics

Properties	Test methods	Tolerance limits
Additive Content	IT-PDE-026	7,000 %
Heat resistance	IT-PDE-009, DIN 53772	Máx. 230 °C
Melt Flow Index of the Carrier Resin	ASTM D1238; IT-PDE-025	3,0 g/10min
Principle agent		Process aid

Monitored Characteristics

Properties	Test methods	Tolerance limits
Physical Form	P-PR-2907	Uniform pellets free from contamination

Regulatory Requirements

Laws/Standards	Limit of Application
(EU) 10/2011 - Foods	No restrictions
94/62/EC	No restrictions
ANVISA 105/99 (RDC 17/08, 52/10, 56/12)	No restrictions
ASTM F 963 - Toys	No restrictions
BfR (Germany)	
CONEG	No restrictions
EN 71-3 - Toys	No restrictions
FDA 21 CFR	
Heavy metal free	
NM 300-3 - Toys	No restrictions
REACH	No restrictions
Resolution AP (89) 1	No restrictions
RoHS - 2011/65/EU	No restrictions

Review reason: Regulatory adjustment

Reason: 4 Date: 05.21.2012

Cromex doesn't use ozone-depleting substances (ODS), volatile organic compounds (VOCs), asbestos, TAA and ITX as masterbatches raw materials.

The technical information and legislation reproduced here represent the best of our experience. However, no liability will be assumed for practical results obtained beyond our control. There are laws and regulations that shall be observed by the customers, being also applicable to third parties. This information does not exempt customers from their liability to check the fitness of our masterbatches to the final product. For further information, refer to our technical support department.



PE-AX 5058 - 6405058

This data was printed on 06.12.2015 and is valid without signature.

The technical information and legislation reproduced here represent the best of our experience. However, no liability will be assumed for practical results obtained beyond our control. There are laws and regulations that shall be observed by the customers, being also applicable to third parties. This information does not exempt customers from their liability to check the fitness of our masterbatches to the final product. For further information, refer to our technical support department.

CROMEX S/A – Unidade São Paulo
Av. Professor Celestino Bourroul, 273 • Limão
São Paulo • SP • CEP: 02710-000
INTERNATIONAL CALLS - Phone: (55 11) 3856.1087

CROMEX S/A – Unidade Bahia
Av. Periférica I, 4312 – Parte A • Centro Ind. Aratú
Simões Filho • BA • CEP: 43700-000

Tel.: (55 11) 3856.1000 • Fax: (55 11) 3966.6973