



BLACK 22951 - 6222951

Product Description

Suggested let down ratio Economical films where the cost is the most important requirement

Recommended dosage 2.0 - 5.0%

Carrier resin LDPE

Concentrate of: Inorganic pigment and mineral filler

Typical Product Characteristics

Properties	Test methods	Tolerance limits
Fastness to Bleeding	DIN 53775 3	5
Heat resistance	P-QM-2603, DIN 53772	Máx. 300 °C
Light Fastness	DIN 53388	8
Melt Flow Index of the Carrier Resin	P-AM-2715, ASTM D 1238	20,0 g/10min

Monitored Characteristics

Properties	Test methods	Tolerance limits
Grade of dispersion	P-PR-2909	D
Physical Form	P-PR-2907	Uniform pellets free from contamination

Regulatory Requirements

Laws/Standards	Limit of Application
94/62/EC	No restrictions
ASTM F 963 - Toys	No restrictions
CONEG	No restrictions
EN 71-3 - Toys	No restrictions
NM 300-3 - Toys	No restrictions
REACH	No restrictions
Resolution AP (89) 1	No restrictions
RoHS - 2002/95/EC	No restrictions

Review reason: Inclusion of regulations

Reason: 8 Date: 06.10.2011

Cromex doesn't use ozone-depleting substances (ODS), volatile organic compounds (VOCs), asbestos, TAA and ITX as masterbatch raw materials.

This data was printed on 07.28.2011 and is valid without signature.

The technical information and legislation reproduced here represent the best of our experience. However, no liability will be assumed for practical results obtained beyond our control. There are laws and regulations that shall be observed by the customers, being also applicable to third parties. This information does not exempt customers from their liability to check the fitness of our masterbatches to the final product. For further information, refer to our technical support department.